



RF1314POS

POINT OF SALE

Ultra slim, small footprint wide screen display design for the hospitality and retail industry. Its shiny and matt contrast finish gives it an outstanding look. No exterior vents and a fanless design to reduce the noise and prevent the dust inside the unit. A variety slim type peripherals perfectly fit in the ID design.

- 14" W display with resistive touch technology
- No exterior vents on back cover
- A front USB for easy service
- Slim type peripherals
- Pole type 2nd display
- A fanless design to reduce the noise and prevent the dust inside



Ultra slim & fanless design to reduce noise and dust inside



14"W LED LCD with Resistive touch technology



Rich I/O port



Small footprint and Slim type peripherals, MSR, VFD, iButton



HDD easy to swap



MOTHERBOARD

C56L D16

Processor	Intel Cedar View D2550 CPU, 1.86 GHz, L2 1MB, TDP 10W	ARM Cortex A9, Dual core CPU, 1GHz
Chipset	Intel NM10	N/A
System Memory	1x DDR3 S.O.DIMM up to 4GB, FSB 1066MHz	1GB DDR3 (RAM file system)
Graphic Memory	Intel GMA 3650 (Gfx frequency up to 640MHz), DX9	N/A
System Storage	N/A	8G (Boot from EMMC)

TOUCH PANEL

LCD Size	14.1" TFT LCD
Brightness	200 nits
Resolution	1366*768
Touch Screen	Resistive or True Flat PCAP Touch

STORAGE

Hard Drive	1x 2.5" SATA HDD	N/A
Flash Memory	1x SATA SSD card (option)	N/A

EXPANSION

MiniPCI-E Socket	1
------------------	---

EXTERNAL I/O

USB	4x USB2.0	4x USB2.0
Serial Port	4x RJ45 (COM1 standard RS232; COM2/3/4 powered RS232) (COM2 default 0V, COM3 default 5V, COM4 default 12V)	4x RJ45 (powered RS232) (COM1/2 default 0V, COM3 default 5V, COM4 default 12V)

LAN	1x RJ45
-----	---------

VGA	1x DB15	N/A
-----	---------	-----

DC Jack	1
---------	---

Micro SD	N/A	1
----------	-----	---

POWER

Power Supply	1
--------------	---

CONTROL

Power Button	1
--------------	---

Indicator LED	1
---------------	---

(OPTIONAL)

MSR	1(USB)
-----	--------

i-Button	1(USB)
----------	--------

Fingerprint	1(USB)
-------------	--------

CERTIFICATE

EMC & Safety	FCC, CE Class A, LVD
--------------	----------------------

ENVIRONMENT

Operating Temperature	0°C ~ 35°C (32°F ~ 95°F)
-----------------------	----------------------------

Storage Temperature	-20°C ~60°C (-4°F ~ 140°F)
---------------------	----------------------------

Humidity	20% - 85% RH non condensing
----------	-----------------------------

COMMUNICATION

Wireless LAN	802.11 b/g/n Wireless LAN card & antenna (option)
--------------	---

Dimension (WxDxH)	LCD 70° tilt angle: 380 x 180 x 276 mm (15"x7.1"x 10.9")
-------------------	--

Weight	3.7 kg (8.13 lbs)
--------	-------------------

Mounting	75 x 75 mm VESA mounting hole for panel PC type
----------	---

OS Supported	Windows® XP Professional, Windows Embedded, Android 4.2
--------------	---

POSReady 2009, Windows XP Embedded, Windows XP Professional for Embedded, WinCE, Windows 7, Linux

