



RX1800MPTR

Mobile Printer

Fashionable appearance
Fashionable appearance, contracted style



Easy paper loading
Quick and easy drop paper design.

Easy to operate
Simple, easy to operate panel design.





RX1800MPTR
Mobile Printer



SPECIFICATIONS

Printing method	Direct thermal
Print speed	50mm / sec
Print width	79.5 ± 0.5mm
Paper roll diameter	≤ 40mm
Paper thickness	0.06~0.08mm
Character per line	576 dots/line
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24x24 dots
Interface	Bluetooth+USB+Serial
Barcode	1D Barcode: UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) / CODABAR/ITF/CODE39/CODE93/CODE128 2D Barcode: QR CODE/PDF417
Extended characters	PC347(Standard Europe/, Katakana, PC850(Multilingual), PC860(Portuguese), PC863(Canadian-French), PC865(Nordic), West Europe, Greek, Hebrew, East Europe, Iran, WPC1252, PC866(Cyrillic#2), PC852(Latin2), PC858(IranII, Latvian, Arabic, PT151(1251)
NV FLASH	64 K Bytes
Input buffer	32 K Bytes
Power supply	Input : AC 110V/240V, 50~60Hz
Power	Output : AC 9V-2A
Battery	2000mAh
Reliability	Printing head life: 50 km
Working environment	Temperature (0~45°c), humidity(10~80%)
Storage environment	Temperature (-10~60°c), humidity(10~90%)
Operating system	Win 9X/Win 2000/Win 2003/Win XP/Win 7/Win 8/Win 10/Linux/IOS/Android
Gross weight	0.21 kg
Dimension	108.5×105×48mm (L×W×H)