



# RF1458POS

Pos All In One





# RF1458POS

Pos All In One



Head thickness= 47.6mm





# RF1458POS

## Pos All In One



### SPECIFICATION

<b>Motherboard</b>	D36V4.0	D86U V2.0
<b>CPU</b>	Intel Bay Trail CPU BGA 1170 (22nm)	Intel Skylake U CPU BGA 1296 (14nm)
	Intel Bay Trail CPU	Celeron 3955U 2GHz, LLC 2M (15W,EIA)
	Celeron J1900 2.4GHz, L2 2M	i3 6100U 2.3GHz, LLC 3M (15W, EIA)
		i5 6300U 2.4GHz, LLC 3M (15W,EIA)
<b>System Memory</b>	1x DDR3L SO DIMMx1 up to 8GB, 1066/1333MHz	DDR3L S.O. DIMM x1, 1600MHz, 2GB max 8GB
<b>Graphic Memory</b>	Intel HD graphic DX11 and OCL1.1	Intel HD Graphic (Gen 9 ) DX12 and OCL4.2
<b>LCD Touch Panel</b>		
<b>LCD Size</b>	18.5" LED ( 1 CH LVDS )	
<b>Brightness</b>	250 nits	
<b>Resolution</b>	1366*768	
<b>Touch Screen</b>	True flat P CAP	
<b>Storage Device</b>		
<b>HDD Drive</b>	1 x 2.5" SATA III SSD	
<b>Flash Memory</b>	Option SATA SSD flash card	
<b>Expansion</b>		
<b>Mini PCI E Slot</b>	1	1
<b>External I/O Ports</b>		
<b>USB 2.0</b>	4	2
<b>USB 3.0</b>	1	4
<b>DC Jack</b>	1	
<b>VGA</b>	1 (12V powered enable by BIOS )	
<b>Giga LAN (10/100/1000)</b>	1	
<b>Cash Drawer (1in 2out)</b>	1 x RJ-11	
<b>RJ 45 COM</b>	3 x RJ 45 COM (COM1 / COM2 W/5V, COM3 W/12V powered enabled by BIOS	
<b>Power</b>		
<b>Power Supply (19V)</b>	65W with D36, 90W with D86U	
<b>Control / Indicator</b>		
<b>Power Button</b>	1	
<b>Power LED</b>	2 (turn on: blue, turn off)	
<b>Peripheral (optional)</b>		
<b>MSR</b>	1(USB) with blade CN	
<b>i-Button</b>	1(USB) with blade CN	
<b>Finger Print</b>	1(USB) with blade CN	
<b>Second Display</b>	10.1" 2nd display (w/o touch)	
<b>Customer Display</b>	LCM (USB)	
<b>Speaker</b>	2 x 2 W	
<b>Stereo Depth Camera Intel RealSense D415)</b>	1 (USB 3.0)	

\*Product specifications subject to change without prior notice