



# RF1730KIO

## Self-service Kiosk Type



### ★ FEATURES

- Multi-OS Support - Windows, Android, Linux
- Multiple peripherals - Expandability & Flexibility
  - Narrow bezel design - Elegant & Stylish
- Flexible configurations - Printer/Floor/POS Stand
  - Modular design - Easy maintenance



# RF1730KIO

## Self-service Kiosk Type



### SPECIFICATION

<b>System</b>	<b>Motherboard</b>	F14	D84U
	<b>Processor</b>	Qualcomm 450	Intel® 3965U      Intel® i3-7100U
	<b>Memory</b>	3GB LPDDR3	4GB DDR4
	<b>Storage</b>	32GB eMMC	128GB SSD
	<b>Supported OS</b>	Android 9.0	Windows 10 IoT Enterprise, Linux
<b>I/O Ports</b>	<b>USB</b>	2x USB3.0 ( Type C ) , 2x USB3.0, 2x USB2.0	2x USB3.0 ( Type C ) , 2x USB3.0, 2x USB2.0
	<b>Serial Port</b>	2x DB9 (Powered RS232) (COM1 0V*/5V, COM2 0V*/12V)	
	<b>LAN</b>	1x RJ45	
	<b>Cash Drawer</b>	1x RJ11	
	<b>DP</b>	2x Proprietary	
	<b>DC Jack</b>	1x 4PIN DIN (with latch)	
<b>Display</b>	<b>Size and Resolution</b>	<b>RF1736KIO</b> : 11.6" 1920 x 1080 ( Full HD )	
		<b>RF1737KIO</b> : 15.6" 1920 x 1080 ( Full HD )	
		<b>RF1738KIO</b> : 18.5" 1366 x 768 ( HD )	
		<b>RF1738KIO</b> : 21.5" 1920 x 1080 ( Full HD )	
	<b>Touch Screen</b>	True-Flat PCAP Multi-touch	
<b>Power</b>	<b>Power Supply</b>	65W / 19V	120W / 19V
<b>Certificate</b>	<b>EMC &amp; Safety</b>	FCC Class A, CE Mark Class A, LVD	
<b>Environment</b>	<b>Operating Temperature</b>	0°C ~ 35°C ( 32°F ~ 95°F )	
	<b>Storage Temperature</b>	-20°C ~ 60°C ( -4°F ~ 140°F )	
	<b>Humidity</b>	20% ~ 85% RH non-condensing	
<b>Option</b>	<b>Pin Pad</b>	Supported Verifone® VX820, P400, Ingenico iPP 325	
	<b>Scanner</b>	2D Scanner	
	<b>Camera</b>	5MP Camera	
	<b>Stand</b>	Printer Stand / Floor Stand	
	<b>Printer</b>	Epson® TM-m30 / TM-T88IV , Star mc-Print3/ TSP-100/TSP-654	