



RH1151DPB-V

POS MONITOR

FEATURE



- 15 inches TFT panel(1024 x 768)
- Elegant flat panel design
- XGA (1024x768) resolution
- Support VGA video input
- Multilingual OSD Menu
- Five UI buttons
- Support VESA mounting
- With mounting forside Programmable MS-R(USB / PS2)
- With mounting forsecond display
- Withoptional ELO touch(USB / RS232)
- Withtwo availablestands:
- Multi-port stand(standard)
- Metal zig-zag stand





RH1151DPB-V POS MONITOR

SPECIFICATION

Panel	Viewing Area	15 inches
	Resolution	1042 x 768
	Active Display Area (mm)	304.128 (w) x 228.096 (H)
	Display Color	16,777,216 colors
	Response Time	8 ms
	Contrast Ratio	600:1
	Viewing Angle	70 (up) / 60 (down) / 75 (left) / 75 (right)
Video Input	Luminance	250 cd/m2
	VGA Signal	RGB analog
Power Adaptor	Input	Universal AC100 - 240V. 50/60 Hz
	Output	DC + 12V,2.5A
Power	Management	VESA DPMS
	Consumption	4W
Environment	Storage Temperature	-25°C - 70°C
	Operating temperature	0°C - 42° C
	Operating Humidity	10% - 85%
Rotation	Vertical	30°
Mounting	Standard	VESA compliant (100mm x 100mm)
Optional	Touch panel	ELO 5-wire resistive, zero bezel type
	MSR	Programmable
	Customer Display	2 - Line LCD display AP701A - 7" TFT Display AP801A - 8" TFT Display