

RM3205SFK

Kiosk







RM3205SFK







RM3205SFK

Kiosk

SPECIFICATION

OS Support	WIN 10 (trial version)		
CPU	I3-6100U		
System Memory	8G		
Disk	258G(SSD)		
Speaker	5W*2		
Interface	USB*3/RJ45*1		
Network	RJ45/WIFI		
Touch screen	Projected Capacitive Touch(10 points)	Response time	10ms
LCD display Type	TFT-LCD	Response time	12ms
Display Screen size	21.5"	Viewing angle	H178° V178°
Max Resolution	1920x1080	Display Colors	16.7M
Aspect Ratio	16:9	Refresh Rate	60Hz
Brightness	300cd/m2	Panel Life	30000 hours
Contrast Ratio	3000:1		
Voltage	AC100V-240V,50/60HZ	Power Consumption	<65W
Optional	Printer (standarded not provided), Card reader holder		
Space for printer	printer is not provided and max size is W150*D150*H200 MM		
Material	SPCC	Surface	Powder coated
Net weight		Overall size	
Color	White, black or customized	Placement	Floor standing
Working temperature	0~40℃	Storage temperature	-20∼60℃
Working humidity	20%~80%	Storage humidity	10%~90%
Application	indoor		