



RM4815TUTMP

“all-in-one” desktop type ticket printer solution





RM4815TUTMP

“all-in-one” desktop type ticket printer solution

SPECIFICATION

Print	Print method	Thermal dot line printing
	Dots	576dots
	Print speed	250mm/s (max)
	Print width	72mm (max)
	Paper roll diameter	150mm(max)
	Paper width	80mm
	Paper thickness	60 - 150um
	Paper feed	Auto feeding(horizontal 180°)
	Cut method	Full/Partial cut
	Print length	100KM
	Print format	Inverse, underline, italic, bold
	Cutter life	1,000,000 cuts
	Baud rate	9600, 19200, 38400, 115200
	Single print min length	80mm
	characters	ASCII
Chinese		24*24
Detect	Print head temperature	Temperature sensor
	Lifter detect	microswitch
	Paper presense detect	mechanical sensor
	Paper out detect	
	Paper low detect	Photo-interrupter
	Black mark detect	
	Cutter detect	
	Seam detect (Send, receive)	Photo electric sensor
	Paper jam/pull detect	24 ± 5% V
	Condition	Working voltage
Average Current		7.5A
Peak Current		RS232, USB
Interface		Thermal paper roll
Paper Type		(Outer paper has thermal layer)
Environment	Operation temperature	-10 - 45°C (No condensation)
	Operation humidity	20% - 80%RH (40°C,80%RH)
	Storage temperature	-20 - 70°C (No condensation)
	Storage humidity	10% - 90%RH (50°C,90%RH)
Dimension	L*W*H	Approx 151mm*229.5mm*364.5mm
	Weight	Approx 5.25kg